

Baku Oil Blue Spiral PVC Suction and Delivery Hose



- Application:** Suitable for light suction and delivery of fuel oils with a low aromatic whether used in applications on plant or tankers. These include lubricating oils, hydraulic oils, diesel, kerosene, white spirit and other petroleum derivatives.
- Working pressure:** 9.7 bar (140psi) to 2 bar (29psi). Safety factor 3:1. Vacuum 0.88 bar to 0.78 bar depending on bore size. Ratings @ 23°C, +/- 2°C.
- Construction:** Blue soft nitrated pvc with embedded shock resistant semi-rigid white pvc spiral helix.
- Branding:** DIXON BAKU OIL HOSE DIXON ASSEMBLY W.P. _____.
- Temperature range:** -15°C to + 60°C.

PART NUMBER	DIMENSIONS MM		PRESSURE BAR			WEIGHT KG/M (APPROXIMATE)	BEND RADIUS MM (APPROXIMATE)	COIL LENGTH METRE
			POSITIVE		VACUUM			
	ID	OD	WORKING	BURST (MIN)				
AUS025BHD	25	33.4	9.7	29.1	0.88	0.485	113	30
AUS032BHD	32	40.8	8	24	0.88	0.580	144	30
AUS038BHD	38	47	8	24	0.88	0.680	171	30
AUS050BHD	51	60.4	6	18	0.88	1.040	230	30
AUS065BHD	63	73.4	5	15	0.88	1.360	284	30
AUS080BHD	76	87.6	4.7	14.1	0.88	1.700	342	30
AUS100BHD	102	115.5	3	9	0.88	2.620	459	30
AUS150BHD	152	167.6	2	6	0.78	4.430	684	10

FOR INSTALLATION AND SAFETY GUIDELINES REFER TO THE TECHNICAL SECTION