

ETALON INTALOMETER 531, Metric Sets

Made to check through holes, blind bores and short centring shoulders. All models covering the application range up to 100 mm have sloped bolts extending beyond the front face of the measuring head.



Models from 10 to 100mm: DIN 863 T4 (Style C2) NFE 11-099



Max. perm. error for models covering the application ranges from 5 to 40 mm = 3 µm 40 to 100 mm = 4 µm 100 to 200 mm = 5 µm



Repeatability limit for models covering the application ranges from 5 to 40 mm = 3 µm 40 to 100 mm = 4 µm 100 to 200 mm = 5 µm



Measuring bolts on models from 5 to 100 mm: hardened steel. 100 to 200 mm: tungsten carbide tipped.



Protective case or carrying case



Inspection report with a declaration of conformity



Identification number



Models from 5 to 100 mm = 0,002 mm on vernier, 100 to 200 mm = 0,01 mm

No	mm	No	Isolated instruments	mm	No	Setting rings	mm	No	Extensions	mm
COMPOSITION OF THE SETS:										
078110592	5 ÷ 10	078112356		5 ÷ 6	00840114	6		078103613	100	
		078112357		6 ÷ 7	00840115	8,5				
		078112358		7 ÷ 8,5						
		078112359		8,5 ÷ 10						
078110594	10 ÷ 20	078112360		10 ÷ 12,5	00840116	12,5		078103621	150	
		078112361		12,5 ÷ 15	00840117	17,5				
		078112362		15 ÷ 17,5						
		078112363		17,5 ÷ 20						
078110596	20 ÷ 40	078112364		20 ÷ 25	00840106	25		078103624	150	
		078112365		25 ÷ 30	00840107	35				
		078112366		30 ÷ 35						
		078112367		35 ÷ 40						
078110598	40 ÷ 100	078112368		40 ÷ 45	00843230	45		078104940	150	
		078112369		45 ÷ 50	00843239	60				
		078112370		50 ÷ 60	00840118	85				
		078112371		60 ÷ 70						
		078112372		70 ÷ 85						
		078112373		85 ÷ 100						