









Tungsten carbide



Wooden case



Declaration of conformity



Identification



0,5 mm



Max. 10 N



8 mm diameter



0,01 mm



0 ≤ 500 mm: malleable cast iror; 500 ≤ 1000 mm: steel tube with insulating grips. Max. flexure of the frame under a measuring force of 10 N: see the table opposite





DIN 863 T3 (Style D16) NF E 11-090



Set includes 2 guard plates for the frame as well as 1 clamping nut

Tungsten carbide tipped



Identification number



8 mm diameter

ISOMASTER AB with Interchangeable Anvils

Lightweight, but rugged anvil micrometers. Set No. 00140101 includes 4 interchangeable anvils with increasing length in steps of 25 mm.

Anvils are adjusted and numbered in pairs, thus rendering any correction of the indication unnecessary whenever an anvil is exchanged.





No		OÈ	///
	mm	μm	μm
00111901	0 ÷ 100	6	3
00111902	100 ÷ 200	7	4,5
00111903	200 ÷ 300	8	7
00111904	300 ÷ 400	9	9
00111905	400 ÷ 500	10	9
OPTIONAL ACCESSORIES:			
00140101	Interchangeable anvils AB1W		
00140301	Dial gauge element for ABY series micro- meters		

Measuring range up to 1500 mm also available upon request.

Interchangeable Anvils for ISOMASTER ABY Series

Set of 4 interchangeable anvils with increasing length in steps of 25 mm. The anvils are adjusted and numbered in pairs, thus eliminating the need for resetting the indication when exchanging either of them. Supplied as standard accessories with the AB series micrometers.



