

Micrometers 0.001 mm, parallax-free

Rugged micrometers with a vernier graduation of 0.001 mm and a favourable price-performance ratio.

- Measuring range: 0-200 mm.
- Vernier: 0.001 mm, parallax-free by enlarged thimble.
- Friction thimble.
- Tungsten carbide measuring faces: $\varnothing 6.5$ mm.

- DIN 863 T1.
- Delivery incl. adjustment tool.
- From measuring range 25-50 mm including setting gauge.



Item No.	Measuring range/mm	Accuracy mm
906.280	0 - 25	± 0.004
906.281	25 - 50	± 0.004
906.282	50 - 75	± 0.005
906.283	75 - 100	± 0.005
906.284	100 - 125	± 0.006
906.285	125 - 150	± 0.006
906.286	150 - 175	± 0.007
906.287	175 - 200	± 0.007

Fast adjustable micrometers

Fast adjustable micrometers because one revolution results in a displacement of 1 mm. The measuring value can be read directly from the 100 step graduation on the thimble.

- Measuring range: 0-200 mm.
- Graduation: 0.01 mm.
- 1 revolution of the thimble = 1 mm.
- Thimble with 100 step graduation.
- Tungsten carbide measuring faces: $\varnothing 8$ mm.

- DIN 863 T1.
- From measuring range 25-50 mm including setting gauge.



Item No.	Measuring range/mm	Accuracy mm
907.000	0 - 25	± 0.004
907.001	25 - 50	± 0.004
907.002	50 - 75	± 0.005
907.003	75 - 100	± 0.005
907.004	100 - 125	± 0.006
907.005	125 - 150	± 0.006
907.006	150 - 175	± 0.007
907.007	175 - 200	± 0.007