


Тип 6F



Тип 6W

HTD® 5M-09

Характеристики	Обозначение	КОД	Тип шкива	Типо-размер реборды	К-во зубьев	Dp, мм	De, мм	Df, мм	Dm, мм	Di, мм	F, мм	L, мм	Диаметр черного отверстия	Масса, кг	
Сталь С45 Е – UNI EN 10083–1	С ребордами	12 5M 09	05M0912	6F	F07	12	19,10	17,96	23	12,0	–	14,5	20,0	4	0,028
		14 5M 09	05M0914	6F	F08	14	22,28	21,14	25	13,0	–	14,5	20,0	6	0,034
		15 5M 09	05M0915	6F	F09	15	23,87	22,73	28	16,0	–	14,5	20,0	6	0,042
		16 5M 09	05M0916	6F	F09	16	25,46	24,32	28	16,5	–	14,5	20,0	6	0,050
		18 5M 09	05M0918	6F	F10	18	28,65	27,51	32	20,0	–	14,5	20,0	6	0,070
		20 5M 09	05M0920	6F	F12	20	31,83	30,69	36	23,0	–	14,5	22,5	6	0,094
		21 5M 09	05M0921	6F	F14	21	33,42	32,28	38	24,0	–	14,5	22,5	6	0,110
		22 5M 09	05M0922	6F	F14	22	35,01	33,87	38	25,5	–	14,5	22,5	6	0,118
		24 5M 09	05M0924	6F	F15	24	38,20	37,06	42	27,0	–	14,5	22,5	6	0,145
		26 5M 09	05M0926	6F	F17	26	41,38	40,24	44	30,0	–	14,5	22,5	6	0,170
		28 5M 09	05M0928	6F	F18	28	44,56	43,42	48	30,5	–	14,5	22,5	6	0,200
		30 5M 09	05M0930	6F	F19	30	47,75	46,60	51	35,0	–	14,5	22,5	6	0,236
		32 5M 09	05M0932	6F	F20	32	50,93	49,79	54	38,0	–	14,5	22,5	8	0,210
		36 5M 09	05M0936	6F	F22	36	57,30	56,16	60	38,0	–	14,5	22,5	8	0,324
40 5M 09	05M0940	6F	F26	40	63,66	62,52	70	38,0	–	14,5	22,5	8	0,400		
Алюминий 6082 T6 UNI 9006/4	Без реборд	44 5M 09	05M0944	6W	–	44	70,03	68,89	–	38,0	54	14,5	25,5	8	0,170
		48 5M 09	05M0948	6W	–	48	76,39	75,25	–	45,0	61	14,5	25,5	8	0,182
		60 5M 09	05M0960	6W	–	60	95,46	94,35	–	45,0	80	14,5	25,5	8	0,230
		72 5M 09	05M0972	6W	–	72	114,59	113,45	–	45,0	100	14,5	25,5	8	0,270

