

Micrometers with a large measuring range

The varnished tubular frame is very stable and equipped with heat insulating grips. With two spacers for a large measuring span.

- Measuring range: 300 - 2000 mm.
- Measuring span:
 - 300 - 1000 mm: 100 mm (travel 25 mm, spacers 25 and 50 mm),
 - 1000 - 2000 mm: 200 mm (travel 50 mm, spacers 50 and 100 mm).
- Graduation: 0.01 mm.
- Rotating spindle.
- Tungsten carbide measuring faces: $\varnothing 8$ mm.
- No-glare chrome finished thimble.
- DIN 863 T3.
- With two setting gauges.

Item No.	Measuring range/mm	Accuracy mm
Measuring span 100 mm:		
906.012	300 - 400	± 0.011
906.013	400 - 500	± 0.013
906.014	500 - 600	± 0.015
906.015	600 - 700	± 0.016
906.016	700 - 800	± 0.018
906.017	800 - 900	± 0.020
906.018	900 - 1000	± 0.020
Measuring span 200 mm:		
906.019	1000 - 1200	± 0.020
906.020	1200 - 1400	± 0.024
906.021	1400 - 1600	± 0.028
906.022	1600 - 1800	± 0.031
906.023	1800 - 2000	± 0.034

