



Тип 6F



Тип 6WF



Тип 6A

HTD® 14M-40

Характеристики	Обозначение	КОД	Тип шкива	Типо-размер реборды	К-во зубьев	Dp, мм	De, мм	Df, мм	Dm, мм	Di, мм	F, мм	L, мм	d, мм	Масса, кг	
Сталь С45 Е – UNI EN 10083–1	С ребордами	28 14M 40	14M4028	6F	F40	28	124,78	122,12	128	100	–	54	69	24	4,73
		29 14M 40	14M4029	6F	F43	29	129,23	126,57	138	100	–	54	69	24	5,09
		30 14M 40	14M4030	6F	F43	30	133,69	130,99	138	100	–	54	69	24	5,45
		32 14M 40	14M4032	6F	F49	32	142,60	139,88	154	100	–	54	69	24	6,17
		34 14M 40	14M4034	6F	F51	34	151,52	148,79	160	100	–	54	69	24	6,88
		36 14M 40	14M4036	6F	F52	36	160,43	157,68	168	100	–	54	69	24	7,60
		38 14M 40	14M4038	6F	F81	38	169,34	166,60	184	120	–	54	69	24	8,28
		40 14M 40	14M4040	6F	F56	40	178,25	175,49	188	120	–	54	69	24	9,26
		44 14M 40	14M4044	6F	F61	44	196,08	193,28	212	120	–	54	69	24	10,32
Литейный чугун EN-GJL-250 UNI EN 1561	С ребордами	48 14M 40	14M4048	6WF	F62	48	213,90	211,11	226	135	170	54	69	24	11,50
		56 14M 40	14M4056	6WF	F66	56	249,55	246,76	256	135	207	54	69	28	13,05
		64 14M 40	14M4064	6WF	F70	64	285,21	282,41	296	135	240	54	69	28	14,40
	Без реборд	72 14M 40	14M4072	6A	–	72	320,86	318,06	–	135	278	54	69	28	16,90
		80 14M 40	14M4080	6A	–	80	356,51	353,71	–	135	314	54	69	28	18,50
		90 14M 40	14M4090	6A	–	90	401,07	398,28	–	135	358	54	69	28	20,00
		112 14M 40	14M4011	6A	–	112	499,11	496,32	–	135	456	54	69	28	26,70
		144 14M 40	14M4014	6A	–	144	641,71	638,92	–	135	600	54	69	28	35,00
		168 14M 40	14M4016	6A	–	168	748,66	745,87	–	135	706	54	69	28	44,20
		192 14M 40	14M4019	6A	–	192	855,62	852,82	–	135	813	54	69	28	52,20
216 14M 40	14M4021	6A	–	216	962,57	959,76	–	150	920	54	69	28	62,50		

