

# Micrometers with prism-shaped anvil

Analog and digital micrometers with prism-shaped anvil for measuring the diameters of objects with an odd number of flutes such as taps, reamers and mills. The angle of the prism aperture is designed for 3-, 5- or 7-fluted workpieces.

- Measuring range: 1-105 mm.
- Analog: graduation 0.01 mm, digital: resolution 0.001 mm.
- Spindle:  $\varnothing 6.5$  mm.
- Tungsten carbide measuring faces. The 906.160 and 907.047 have a pointed spindle for the smallest objects.
- Varnished frame.
- Delivery with a setting standard.

## Digital

- mm/inch conversion.
- ABS/INC switchable.
- Automatic switch-off.
- Reset/preset.
- Power supply: 1 battery type V357.



906.161



907.048



906.160/907.047

Item No.	Measuring range/mm	Accuracy mm	Price	Item No.
<b>For 3-fluted objects, analog:</b>				<b>Digital:</b>
906.160	1- 15	$\pm 0.004$		907.047
906.161	5- 20	$\pm 0.004$		907.048
906.162	20- 35	$\pm 0.005$		907.049
906.163	35- 50	$\pm 0.005$		907.050
906.164	50- 65	$\pm 0.006$		907.051
906.165	65- 80	$\pm 0.006$		907.052
907.060	80- 95	$\pm 0.007$		907.053
<b>For 5-fluted objects, analog:</b>				<b>Digital:</b>
906.166	5- 25	$\pm 0.004$		909.350
906.167	25- 45	$\pm 0.005$		909.351
906.168	45- 65	$\pm 0.006$		909.352
906.169	65- 85	$\pm 0.007$		909.353
907.061	85-105	$\pm 0.008$		909.354
<b>For 7-fluted objects, analog:</b>				<b>Digital:</b>
906.170	5- 25	$\pm 0.004$		909.355
906.171	25- 45	$\pm 0.005$		909.356
906.172	45- 65	$\pm 0.006$		909.357
906.173	65- 85	$\pm 0.007$		909.358
<b>Option:</b>				
836.535	Spare battery			

## Setting standards

Item No.	$\varnothing$ mm
909.323	5
909.324	20
909.325	25
909.326	35
909.327	45
909.328	50
909.329	65
909.330	80
909.331	85



909.326