



Tipo Type	Dimensioni mm/pollici Dimensions mm/inch								Bull. fiss. Bolt Size mm/inch	BPP-SA		Cuscinetto Bearing	Peso Weight (kg)	BPP-SB		Cuscinetto Bearing	Peso Weight (kg)	Supporto Housing	Coefficienti di carico (N) Load ratings (N)	
	d	h	a	e	b	s	g	w		B ₁	n			B ₁	n				Dinamico C Dynamic C	Statico C ₀ Static C ₀
BPP-SA BPP-SB 201 201-8	12 3/4	22,2 7/8	86 3 3/8	68 2 3/4	25 6 3/4	9,5 3/8	3,2 1/8	43,8 1 23/32	M8 5/16	28,6 1,1260	6,5 0,2559	SA201 SA201-8	0,19	22 0,8661	6 0,2362	SB201 SB201-8	0,19	PP203	9 200	4 480
BPP-SA BPP-SB 202 202-9 202-10	15 9/16 5/8	22,2 7/8	86 3 3/8	68 2 3/4	25 6 3/4	9,5 3/8	3,2 1/8	43,8 1 23/32	M8 5/16	28,6 1,1260	6,5 0,2559	SA202 SA202-9 SA202-10	0,19	22 0,8661	6 0,2362	SB202 SB202-9 SB202-10	0,19	PP203	9 200	4 480
BPP-SA BPP-SB 203 203-11	17 1 1/16	22,2 7/8	86 3 3/8	68 2 3/4	25 6 3/4	9,5 3/8	3,2 1/8	43,8 1 23/32	M8 5/16	28,6 1,1260	6,5 0,2559	SA203 SA203-11	0,19	22 0,8661	6 0,2362	SB203 SB203-11	0,19	PP203	9 200	4 480
BPP-SA BPP-SB 204 204-12	20 3/4	25,4 1	98 3 27/32	76 2 63/64	32 1 1/4	9,5 3/8	3,2 1/8	50,5 1 63/64	M8 5/16	31 1,2204	7,5 0,2953	SA204 SA204-12	0,23	25 0,9843	7 0,2756	SB204 SB204-12	0,23	PP204	12 200	6 300
BPP-SA BPP-SB 205 205-13 205-14 205-15 205-16	25 1 9/16 7/8 1 5/16 1	28,6 1 1/8	108 4 1/4	86 3 25/64	32 1 1/4	11,5 29/64	4 0,157	56,6 2 15/64	M10 3/8	31 1,2204	7,5 0,2953	SA205 SA205-13 SA205-14 SA205-15 SA205-16	0,32	27 1,0630	7,5 0,2953	SB205 SB205-13 SB205-14 SB205-15 SB205-16	0,28	PP205	13 300	7 460
BPP-SA BPP-SB 206 206-17 206-18 206-19 206-20	30 1 1/16 1 1/8 1 3/16 1 1/4	33,3 1 5/16	117 4 39/64	95 3 47/64	38 1 1/2	11,5 29/64	4 0,157	66,3 2 39/64	M10 3/8	35,7 1,4055	9 0,3543	SA206 SA206-17 SA206-18 SA206-19 SA206-20	0,50	30 1,1811	8 0,3150	SB206 SB206-17 SB206-18 SB206-19 SB206-20	0,47	PP206	18 500	10 800
BPP-SA BPP-SB 207 207-20 207-21 207-22 207-23	35 1 1/4 1 5/16 1 3/8 1 7/16	39,7 1 9/16	129 5 5/64	106 4 5/32	42 1 21/32	11,5 29/64	4,6 0,181	78 3 1/8	M10 3/8	38,9 1,5315	9,5 0,3740	SA207 SA207-20 SA207-21 SA207-22 SA207-23	0,71	32 1,2598	8,5 0,3346	SB207 SB207-20 SB207-21 SB207-22 SB207-23	0,57	PP207	24 500	14 600

Disponibile in acciaio inox Supporto: AISI 304 - Cuscinetto: AISI 440C
Available stainless steel Housing: AISI 304 - Bearing: AISI 440C