

Tipo Type Modelle	$d_{H7}$ mm	D mm	L mm	$B_1$ mm	$L_1$ mm	$b_2$ mm	$l_2$ mm	$l_3$ mm	$l_4$ mm	Peso Weight Masse Kg	$n_{MAX}$ (min <sup>-1</sup> ) Anello interno Inner race Bague intérieure	$T_N$ Nm
GVG 20	20	106	48	40	15	18	35	10,5	113	2,5	400	606
GVG 25	25	106	48	40	15	18	35	10,5	113	2,4	400	606
GVG 30	30	106	48	40	15	18	35	10,5	113	2,3	400	606
GVG 35	35	106	48	40	15	18	35	10,5	113	2,2	400	606
GVG 40	40	132	52	60	15	18	35	10	125	4,0	300	1295
GVG 45	45	132	52	60	15	18	35	10	125	3,8	300	1295
GVG 50	50	132	52	60	15	18	35	10	125	3,7	300	1295
GVG 55	55	132	52	60	15	18	35	10	125	3,5	300	1295
GVG 60	60	161	54	70	15	18	35	10	140	6,1	250	2550
GVG 70	70	161	54	70	15	18	35	10	140	5,7	250	2550
GVG 80	80	190	70	70	20	25	45	15	165	10,2	200	4875
GVG 90	90	190	70	70	20	25	45	15	165	9,6	200	4875

**IT**

$T_{MAX} = 2 \times T_N$   
Cava DIN 6885 foglio 1  
1) Velocità massima consentita

**EN**

$T_{MAX} = 2 \times T_N$   
Keyway DIN 6885 page 1  
1) Maximum allowed speed

**FR**

$T_{MAX} = 2 \times T_N$   
Rainure DIN 6885 page 1  
1) Vitesse maximale consentie

