

Digital micrometers IP54 with pin-shaped anvil

Digital micrometers for measuring e.g. (tube) wall thickness.

- Measuring range: 0- 50 mm.
- Resolution: 0.001 mm.
- mm/inch conversion.
- ABS/INC switchable.
- Automatic switch-off (except 907.036).
- Reset/preset.
- Adjustable tolerance limits (only 907.036).
- Pin-shaped anvil: \varnothing 1.8 mm.
- Tungsten carbide measuring faces.
- Varnished frame.
- Protection: IP54.
- Power supply: 1 battery type V357.



907.036

Item No.	Measuring range/mm	Accuracy mm
907.036	0-25	± 0.006
907.037	25-50	± 0.006
Option:		
836.535	Spare battery	

Digital micrometers with special measuring jaws

Digital micrometers with special measuring jaws for measurements in hard-to-reach places such as cut-outs in workpieces, gear pitches, etc.

- Measuring range: 0- 175 mm.
- Resolution: 0.001 mm.
- mm/inch conversion.
- ABS/INC switchable.
- Automatic switch-off (except 906.131).
- Reset/preset.
- Non-rotating spindle.
- Adjustable tolerance limits (only 906.131).
- Varnished frame.
- Power supply: 1 battery type V357.



906.131

Item No.	Measuring range/mm	Accuracy mm
906.131	0- 25	± 0.004
906.132	25- 50	± 0.004
906.133	50- 75	± 0.005
906.134	75- 100	± 0.005
906.592	100- 125	± 0.006
906.593	125- 150	± 0.006
906.594	150- 175	± 0.007
Option:		
836.535	Spare battery	