





Deep Groove Ball Bearing

d 130~140 mm



Principal dimensions				Basic load ratings		Limit speed ratings	
d	D	B	r <sub>min</sub>	C <sub>r</sub>	C <sub>or</sub>	Grease	Oil
mm				kN		r/min	
<b>130</b>	180	24	1.5	65.0	67.0	3400	4000
	190	19	0.7	56.0	60.0	3200	3800
	190	19	0.7	56.0	60.0	3200	3800
	200	22	1.1	79.5	81.5	3200	3800
	200	22	1.1	79.5	81.5	3200	3800
	200	33	2	109	98	3200	3800
	200	33	2	109	98	3200	3800
	200	33	2	109	98	3200	3800
	200	33	2	109	98	3200	3800
	230	40	3	153	134	2600	3200
	230	40	3	153	134	2600	3200
	230	40	3	153	134	2600	3200
	230	40	3	165	148	2600	3200
	230	40	3	165	148	2600	3200
	230	40	3	153	134	2600	3200
	280	58	4	251	241	2200	2600
	280	58	4	230	216	2200	2600
	280	58	4	240	226	2200	2800
	280	58	4	251	241	2200	2600
	280	58	4	251	241	2200	2600
	280	58	4	251	241	2200	2600
	280	58	4	251	241	2200	2600
	280	58	4	251	241	2200	2600
	280	58	4	230	216	2200	2600
<b>140</b>	175	18	1.1	37.0	40.0	3400	4000
	175	18	1.1	37.0	40.0	3400	4000
	190	24	1.5	64.0	67.5	3200	3800
	210	22	1.1	80.5	86.5	3000	3600
	210	33	2	106	102	3000	3600
	210	33	2	106	102	3000	3600
	210	33	2	106	102	3000	3600
	210	33	2	106	102	3000	3600
	250	42	3	166	150	2400	3000
	250	42	3	166	150	2400	3000
	250	42	3	166	150	2400	3000
	250	42	3	128	150	2400	3000

Designations	Abutment and fillet dimensions			Weight
	D <sub>smin</sub>	dh <sub>max</sub>	r <sub>amax</sub>	
	mm			kg
<b>61926</b>	138	172	1.5	1.56
<b>726</b>	134	186	0.7	1.70
<b>726H</b>	134	186	0.7	1.91
<b>16026M</b>	136.5	193.5	1	2.32
<b>16026</b>	136.5	193.5	1	2.19
<b>6026</b>	139	191	2	3.29
<b>FL-6026</b>	139	191	2	3.29
<b>6026M</b>	139	191	2	3.96
<b>6026MA</b>	139	191	2	3.98
<b>6226</b>	143	217	2.5	6.33
<b>6226M/CRA9</b>	144	216	2.5	7.83
<b>6226/W124</b>	144	216	2.5	6.33
<b>226HU1</b>	143	217	2.5	7.51
<b>226U1</b>	143	217	2.5	6.16
<b>6226MA</b>	143	217	2.5	7.91
<b>6326</b>	146	264	3	15.3
<b>6326-DT</b>	146	264	3	15.1
<b>6326/W124</b>	147	263	3	15.3
<b>6326A</b>	146	264	3	14.9
<b>6326F1/HQ1</b>	146	264	3	16.7
<b>FL-6326/HQ1</b>	146	264	3	13.5
<b>6326M</b>	146	264	3	18.3
<b>6326M-DT</b>	146	264	3	17.6
<b>61828M</b>	146.5	168.5	1	1.00
<b>61828MA</b>	146.5	168.5	1	0.933
<b>61928M</b>	148	182	1.5	2.11
<b>16028M</b>	146.5	203.5	1	3.08
<b>6028</b>	146.5	201	2	3.47
<b>6028/C9</b>	149	201	2	3.47
<b>6028/C9YB2</b>	149	201	2	3.47
<b>6028M</b>	149	201	2	4.20
<b>6228</b>	153	237	2.5	7.41
<b>6228/W124</b>	154	236	2.5	7.41
<b>6228M</b>	153	237	2.5	9.28
<b>6228MA</b>	153	237	2.5	9.50