



Codice	D	H	G	M x 1	Rigidezza 45 IRHD (daN/mm)	Rigidezza 60 IRHD (daN/mm)	Rigidezza 70 IRHD (daN/mm)	Deflessione statica max. (mm)
Item	D	H	G	M x 1	Stiffness 45 IRHD (daN/mm)	Stiffness 60 IRHD (daN/mm)	Stiffness 70 IRHD (daN/mm)	Max static deflection (mm)
<b>MMSG1015410</b>	10	15	6	M4X10	1,6	2,4	3,3	3,0
<b>MMSG1214410</b>	12	14	7	M4X10	2,0	3,0	4,2	2,8
<b>MMSG1214510</b>	12	14	7	M5X10	2,0	3,0	4,2	2,8
<b>MMSG1615510</b>	16	15	12,5	M5X10	3,4	6,5	10,1	3,0
<b>MMSG201918</b>	20	19	14,5	M6X18	4,0	6,0	8,2	3,8
<b>MMSG252018P</b>	25	20	10	M6X18	2,8	4,2	5,8	4,0
<b>MMSG252018G</b>	25	20	17	M6X18	4,8	7,3	10,2	4,0
<b>MMSG302020</b>	30	20	24	M8X20	6,8	10,1	14,0	4,0
<b>MMSG403023P</b>	40	30	15	M8X23	4,1	6,0	8,2	6,0
<b>MMSG403023G</b>	40	30	27	M8X23	7,0	10,5	14,4	6,0
<b>MMSG606025</b>	60	60	50	M10X25	13,9	20,6	28,4	12,0