

Micrometers with dial indicator

Micrometers with adjustable anvil and clamping shaft for a dial indicator. Especially suitable for Go/NoGo judgement and batch measurements.

- Measuring range: 0 - 175 mm.
- Graduation thimble and dial indicator: 0.01 mm.
- Range adjustable anvil: 8 mm.
- Trigger for (fast) adjustment.
- Tungsten carbide measuring faces.
- Can also be used in combination with various other dial indicators with clamping stem $\varnothing 8$ mm.



Item No.	Measuring range/mm	Accuracy mm
907.008	0 - 25	± 0.004
907.009	25 - 50	± 0.004
907.010	50 - 75	± 0.005
907.011	75 - 100	± 0.005
907.012	100 - 125	± 0.006
907.013	125 - 150	± 0.006
907.014	150 - 175	± 0.007

Mini-micrometer

- Measuring range: 0 - 15 mm.
- Graduation: 0.01 mm.
- Without friction thimble.
- Dimensions:
total length: 70 mm,
throat depth: 14 mm.



Item No.	Measuring range/mm
906.180	0 - 15

Micrometer with an extra large measuring range

The measuring range of this micrometer can be 'switched' from 25 - 50 to 0 - 25 mm by easy mounting of the prolonged anvil.

- Measuring range: 0 - 50 mm.
- Graduation: 0.01 mm.
- Accuracy: ± 0.004 mm.
- Tungsten carbide measuring faces.
- Delivery incl. adjustment tool and prolonged anvil.



Item No.	Measuring range/mm	Accuracy mm
906.567	0 - 50	± 0.004