Dial indicators 0.01 mm

Indicators with a large measuring range. Shockproof design

- Measuring range: 0 100 mm.
- Graduation: 0.01 mm.
- Clamping stem: Ø8 mm.
- Rotatable dial.
- Shockproof.
- Adjustable tolerance markers (except 907.916).
- Locking screw.
- Flat back.

Item No.

■ Delivery with an inspection report.

Measuring

suring rang	ge. Shockpr	oof design.		- 1	
m.		N TO THE REST OF T			
Dial	934		907.936		
ø/mm 60 60 76 80		907.935			
		PRICE			907.916

range/mm ø/mn 0 - 25 60 907.934 0 - 30 907.935 60 907.936 0 - 50 76 907.916 0 - 10080 **Options:** 908.9871 Back with lug

908.988² Back with lug

Splashproof dial indicators 0.01 mm

Indicators with splashproof design.

- Measuring range: 0-10 mm.
- Graduation: 0.01 mm.
- Clamping stem: Ø8 mm.
- Dial diameter: 55 mm.
- Rotatable dial.
- Shockproof.
- Adjustable tolerance markers.
- Locking screw.
- Back with lug.
- Protection: IP54.
- Conforms to factory standard.

Item No.	Measuring range/mm	
908.777 908.778 908.779	0 - 3 0 - 5 0 - 10	



¹ For 907.934/935. ² For 907.936/916.