





Deep Groove Ball Bearing

d 150~170 mm



Principal dimensions				Basic load ratings		Limit speed ratings	
d	D	B	r _{min}	C _r	C _{or}	Grease	Oil
mm				kN		r/min	
150	320	65	4	277	280	1800	2200
	320	65	4	277	280	1900	2400
160	200	20	1.1	49.5	59	2600	3200
	220	28	2	89	90.0	2600	3200
	229.5	33	3	108	111	2500	3100
	240	25	1.5	94.0	104	2400	3000
	240	25	1.5	94.0	104	2400	3000
	240	38	2.1	143	138	2400	3000
	240	38	2.1	143	138	2400	3000
	240	38	2.1	143	138	2400	3000
	240	38	2.1	127	127	2400	3000
	290	48	3	210	210	1900	2400
	290	48	3	200	201	1900	2400
	290	48	3	202	201	1900	2400
	290	48	3	200	201	1900	2400
	290	48	3	200	201	1900	2400
	290	48	3	202	202	1900	2400
	340	68	4	310	325	1800	2200
	340	68	4	310	325	1800	2200
	340	68	4	310	325	1800	2200
340	68	4	310	325	1800	2200	
340	68	4	238	325	1800	2200	
340	68	4	310	325	1800	2200	
165	250.5	35	2.5	147	143	2200	2600
170	215	22	1.1	65.0	61.0	2600	3200
	215	22	1.1	65.0	61.0	2600	3200
	215	22	1.1	65.0	61.0	2600	3200
	230	28	2	115	100	2400	3000
	230	28	2	115	100	2400	3000
	260	28	1.5	119	128	2200	2800
	260	28	1.5	119	129	2200	2800
	260	42	2.1	161	166	2200	2800
	260	42	2.1	161	166	2200	2800

Designations	Abutment and fillet dimensions			Weight
	D _{smin}	dh _{max}	r _{amax}	
	mm			kg
6330M	166	304	3	23.9
6330M/W124	167	303	3	26.0
61832M	168	192	1.1	1.32
61932M	169	211	2	3.28
62932X3M/YA6	168	211	3	4.67
16032	168	232	1.5	3.95
16032M	168	232	1.5	4.60
6032	171	229	2	5.04
6032/C9	171	229	2	5.04
6032M	171	229	2	6.04
6032M/W124	169	231	2	6.04
6232	173	277	2.5	12.4
6232-DT	173	277	2.5	12.3
6232M	173	277	2.5	14.2
6232M/P59Z2	174	276	2.5	14.4
6232M/CRA9	174	276	2.5	14.2
6232/W124	174	276	2.5	12.3
6332	177	323	3	25.7
6332-DT	177	323	3	26.5
6332M	176	324	3	30.7
6332M-DT	176	324	3	31.8
6332M/W124	177	323	3	30.5
6332/W124	176	324	3	25.7
733	177	238	2.5	6.44
61834M	176.5	208.5	1	2.03
61834M-Z/YA8	176.5	208.5	1	1.89
61834MA	176.5	208.5	1	1.98
61934M	179	221	2	3.42
61934MA	179	221	2	3.40
16034	178	252	1.5	5.01
16034M	178	252	1.5	5.83
6034M	181	249	2	7.96
6034MA	181	249	2	8.25