



Тип 1F



Тип 6F



Тип 6

HTD® 3М-09

Характеристики		Обозначение	КОД	Тип шкива	Типо-размер реборды	К-во зубьев	Dr, мм	De, мм	Df, мм	Dm, мм	F, мм	L, мм	Диаметр черного отверстия	Масса, кг
Алюминий 6082 T6 UNI 9006/4	С ребордами	10 3М 09	03М0910	1F	F01	10	9,55	8,79	13,0	6,0	10,2	17,5	4	0,004
		12 3М 09	03М0912	1F	F02	12	11,46	10,70	15,0	8,0	10,2	17,5	4	0,006
		14 3М 09	03М0914	1F	F03	14	13,37	12,61	16,0	9,5	10,2	17,5	4	0,007
		15 3М 09	03М0915	1F	F04	15	14,32	13,56	17,5	11,6	10,2	17,5	4	0,008
		16 3М 09	03М0916	6F	F05	16	15,28	14,52	18,0	10,0	12,8	20,6	4	0,007
		18 3М 09	03М0918	6F	F06	18	17,19	16,43	20,0	11,0	12,8	20,6	6	0,008
		20 3М 09	03М0920	6F	F07	20	19,10	18,34	23,0	13,0	12,8	20,6	6	0,010
		21 3М 09	03М0921	6F	F08	21	20,05	19,29	25,0	13,0	12,8	20,6	6	0,013
		22 3М 09	03М0922	6F	F08	22	21,01	20,25	25,0	13,0	12,8	20,6	6	0,014
		24 3М 09	03М0924	6F	F08	24	22,92	22,16	25,0	13,0	12,8	20,6	6	0,016
		26 3М 09	03М0926	6F	F09	26	24,83	24,07	28,0	16,0	12,8	20,6	6	0,018
		28 3М 09	03М0928	6F	F10	28	26,74	25,98	32,0	18,0	12,8	20,6	6	0,024
		30 3М 09	03М0930	6F	F10	30	28,65	27,89	32,0	20,0	12,8	20,6	6	0,028
		32 3М 09	03М0932	6F	F12	32	30,56	29,80	36,0	22,0	12,8	20,6	6	0,032
		36 3М 09	03М0936	6F	F14	36	34,38	33,62	38,0	26,0	13,4	22,2	6	0,045
		40 3М 09	03М0940	6F	F15	40	38,20	37,44	42,0	28,0	13,4	22,2	6	0,055
		44 3М 09	03М0944	6F	F18	44	42,02	41,26	48,0	33,0	13,4	22,2	6	0,074
	Без реборд	48 3М 09	03М0948	6	—	48	45,84	45,08	—	33,0	13,4	22,2	8	0,074
		60 3М 09	03М0960	6	—	60	57,30	56,54	—	33,0	13,4	22,2	8	0,106
		72 3М 09	03М0972	6	—	72	68,75	67,99	—	33,0	13,4	22,2	8	0,145

HTD® 3М-15

Характеристики		Обозначение	КОД	Тип шкива	Типо-размер реборды	К-во зубьев	Dr	De	Df	Dm	F	L	Диаметр черного отверстия	Масса, кг
Алюминий 6082 T6 UNI 9006/4	С ребордами	10 3М 15	03M1510	1F	F01	10	9,55	8,79	13,0	6,0	17,0	26	4	0,006
		12 3М 15	03M1512	1F	F02	12	11,46	10,70	15,0	8,0	17,0	26	4	0,008
		14 3М 15	03M1514	1F	F03	14	13,37	12,61	16,0	9,5	17,0	26	4	0,010
		15 3М 15	03M1515	1F	F04	15	14,32	13,56	17,5	11,6	17,0	26	4	0,012
		16 3М 15	03M1516	6F	F05	16	15,28	14,52	18,0	10,0	19,5	26	4	0,010
		18 3М 15	03M1518	6F	F06	18	17,19	16,43	20,0	11,0	19,5	26	6	0,012
		20 3М 15	03M1520	6F	F07	20	19,10	18,34	23,0	12,0	19,5	26	6	0,014
		21 3М 15	03M1521	6F	F08	21	20,05	19,29	25,0	13,0	19,5	26	6	0,016
		22 3М 15	03M1522	6F	F08	22	21,01	20,25	25,0	13,0	19,5	26	6	0,018
		24 3М 15	03M1524	6F	F08	24	22,92	22,16	25,0	13,0	19,5	26	6	0,020
		26 3М 15	03M1526	6F	F09	26	24,83	24,07	28,0	16,0	19,5	26	6	0,027
		28 3М 15	03M1528	6F	F10	28	26,74	25,98	32,0	18,0	19,5	26	6	0,030
		30 3М 15	03M1530	6F	F10	30	28,65	27,89	32,0	20,0	19,5	26	6	0,035
		32 3М 15	03M1532	6F	F12	32	30,56	29,80	36,0	22,0	19,5	26	6	0,042
		36 3М 15	03M1536	6F	F14	36	34,38	33,62	38,0	26,0	20,0	30	6	0,060
		40 3М 15	03M1540	6F	F15	40	38,20	37,44	42,0	28,0	20,0	30	6	0,075
		44 3М 15	03M1544	6F	F18	44	42,02	41,26	48,0	33,0	20,0	30	6	0,095
	Без реборд	48 3М 15	03M1548	6	—	48	45,84	45,08	—	33,0	20,0	30	8	0,103
		60 3М 15	03M1560	6	—	60	57,30	56,54	—	33,0	20,0	30	8	0,150
		72 3М 15	03M1572	6	—	72	68,75	67,99	—	33,0	20,0	30	8	0,212