



Тип 1F



Тип 6F



Тип 6

HTD® 3M-06

Характеристики		Обозначение	КОД	Тип шкива	Типо-размер реборды	К-во зубьев	Dr, мм	De, мм	Df, мм	Dm, мм	F, мм	L, мм	Диаметр черного отверстия
Алюминий 6082 T6 UNI 9006/4	С ребордами	10 3М 06	03М0610	1F	F01	10	9,55	8,79	13,0	6,0	7,2	14,5	4
		12 3М 06	03М0612	1F	F02	12	11,46	10,70	15,0	8,0	7,2	14,5	4
		14 3М 06	03М0614	1F	F03	14	13,37	12,61	16,0	9,5	7,2	14,5	4
		153М 06	03М0615	1F	F04	15	14,32	13,56	17,5	11,6	7,2	14,5	4
		16 3М 06	03М0616	6F	F05	16	15,28	14,52	18,0	10,0	9,8	17,5	4
		18 3М 06	03М0618	6F	F06	18	17,19	16,43	20,0	11,0	9,8	17,5	6
		20 3М 06	03М0620	6F	F07	20	19,10	18,34	23,0	13,0	9,8	17,5	6
		21 3М 06	03М0621	6F	F08	21	20,05	19,29	25,0	13,0	9,8	17,5	6
		22 3М 06	03М0622	6F	F08	22	21,01	20,25	25,0	13,0	9,8	17,5	6
		24 3М 06	03М0624	6F	F08	24	22,92	22,16	25,0	13,0	9,8	17,5	6
		26 3М 06	03М0626	6F	F09	26	24,83	24,07	28,0	16,0	9,8	17,5	6
		28 3М 06	03М0628	6F	F10	28	26,74	25,98	32,0	18,0	9,8	17,5	6
		30 3М 06	03М0630	6F	F10	30	28,65	27,89	32,0	20,0	9,8	17,5	6
		32 3М 06	03М0632	6F	F12	32	30,56	29,80	36,0	22,0	9,8	17,5	6
		36 3М 06	03М0636	6F	F14	36	34,38	33,62	38,0	26,0	10,3	18,0	6
		40 3М 06	03М0640	6F	F15	40	38,20	37,44	42,0	28,0	10,3	18,0	6
		44 3М 06	03М0644	6F	F18	44	42,02	41,26	48,0	33,0	10,3	18,0	6
	Без реборд	48 3М 06	03М0648	6	—	48	45,84	45,08	—	33,0	10,3	18,6	8
		60 3М 06	03М0660	6	—	60	57,30	56,54	—	33,0	10,3	18,6	8
		72 3М 06	03М0672	6	—	72	68,75	67,99	—	33,0	10,3	18,6	8