



| Codice | D | H | M x 1 | Rigidezza 45 IRHD (daN/mm) | Rigidezza 60 IRHD (daN/mm) | Rigidezza 70 IRHD (daN/mm) | Deflessione statica max. (mm) |
|--------------------|-----|-----|--------|----------------------------------|----------------------------------|----------------------------------|-------------------------------------|
| Item | D | H | M x 1 | Stiffness 45 IRHD (daN/mm) | Stiffness 60 IRHD (daN/mm) | Stiffness 70 IRHD (daN/mm) | Max static deflection (mm) |
| PMP242518 | 24 | 25 | M6X18 | 5,6 | 8,2 | 11,4 | 5,0 |
| PMP243518 | 24 | 35 | M6X18 | 3,5 | 5,1 | 7,1 | 7,0 |
| PMP303014 | 30 | 30 | M6X14 | 4,9 | 7,2 | 9,9 | 6,0 |
| PMP303614 | 30 | 36 | M6X14 | 5,5 | 8,0 | 10,8 | 7,2 |
| PMP453023 | 45 | 30 | M8X23 | 12,8 | 12,8 | 12,8 | 6,0 |
| PMP505023 | 50 | 50 | M8X23 | 5,7 | 7,1 | 10,1 | 10,0 |
| PMP505025 | 50 | 50 | M10X25 | 5,7 | 7,1 | 10,1 | 10,0 |
| PMP506733 | 50 | 67 | M8X33 | 4,9 | 7,1 | 9,8 | 13,4 |
| PMP606037 | 60 | 60 | M12X37 | 13,0 | 19,1 | 26,3 | 12,0 |
| PMP1008344 | 100 | 83 | M16X44 | 29,4 | 43,0 | 59,3 | 16,6 |
| PMP1009531 | 100 | 95 | M12X31 | 9,4 | 18,8 | 28,3 | 19,0 |
| PMP1009544 | 100 | 95 | M16X44 | 9,4 | 18,8 | 28,3 | 19,0 |
| PMP10012031 | 100 | 120 | M12X31 | 7,0 | 14,0 | 21,0 | 24,0 |
| PMP10012044 | 100 | 120 | M16X44 | 7,0 | 14,0 | 21,0 | 24,0 |