

Internal measuring instruments

- Measuring range: 6-450 mm.
- Read-out depends on the type of dial indicator.
- Incl. standard dial indicator 0-3 mm/0.01 mm.
- Clamping shaft: $\varnothing 8$ mm.
- Self-centering (except 907.230).
- Interchangeable measuring inserts with tungsten carbide stylus tip (907.230 with spherical measuring face).
- Also suitable for various dial indicators from e.g. Mitutoyo, TESA, Käfer and Peacock with clamping stem $\varnothing 8$ mm.

| Item No. | Measuring range/mm | Measuring depth/mm |
|----------|--------------------|--------------------|
| 907.230 | 6- 10 | 40 |
| 907.231 | 10- 18 | 100 |
| 907.232 | 18- 35 | 125 |
| 907.233 | 35- 50 | 150 |
| 907.235 | 50-160 | 150 |
| 907.236 | 160-250 | 400 |
| 907.237 | 250-450 | 400 |



NEW



907.235+907.933



910.004

Optional dial indicators

| Item No. | Measuring range/mm | Read-out mm | Accuracy mm |
|--|--------------------|-------------|-------------|
| Analog: | | | |
| 907.933 | 0-10 | 0.01 | - |
| Digital (with determination of the reversal point): | | | |
| 907.879 | 0-12.7 | 0.001 | ± 0.01 |
| 907.878 | 0-12.7 | 0.001 | ± 0.005 |
| 909.250 | 0-12.5 | 0.002 | ± 0.015 |
| 909.251 | 0-12.5 | 0.001 | ± 0.006 |
| 910.004 | 0-12.7 | 0.001 | ± 0.004 |



907.879/878



909.250/251