




LLTHC 15 SU TO P5


Slim-line carriage, short length, standard height











Size:	15
W1 [mm]:	34
N [mm]:	9.5
H [mm]:	24
H2 [mm]:	4.2
H3 [mm]:	4.6
L1 [mm]:	47.6
L2 [mm]:	25.6
L3 [mm]:	
L4 [mm]:	4.3
W3 [mm]:	26

Date: 19/02/2019

The contents of this report are the copyright of the publisher and may not be reproduced (even extracts) unless permission is granted. Every care has been taken to ensure the accuracy of the information contained in this report but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

 $[\]ensuremath{^{\circledR}}$ SKF is a registered trademark of the SKF Group.

[©] SKF 2010



Product data sheet

LLTHC 15 SU TO P5

Slim-line carriage, short length, standard height

H4 [mm]:	3.8
H5 [mm]:	4.3
D3 [mm]:	
S2:	M4
W [mm]:	15
H1 [mm]:	14
H6 [mm]:	8.5
F [mm]:	60
D1 [mm]:	4.5
D2 [mm]:	7.5
Emin [mm]:	10
Emax [mm]:	50
Lmax [mm]:	3920
Weight [kg]:	0.1
Weight [kg/m]:	1.4
C [N]:	5800
CO [N]:	9000
Mx[Nm]:	39
Mx0[Nm]:	60
M y/z[Nm]:	21
M y0/z0[Nm]:	32
Preload class:	Zero preload TO
Precision class:	Standard P5

Date: 19/02/2019