





Deep Groove Ball Bearing

d 110~130 mm



Principal dimensions				Basic load ratings		Limit speed ratings	
d	D	B	r _{min}	C _r	C _{or}	Grease	Oil
mm				kN		r/min	
110	240	50	3	195	167	2600	3200
	240	50	3	195	167	2600	3200
	240	50	3	205	176	2400	3000
	240	50	3	205	176	2400	3000
	240	50	3	195	167	2600	3200
	280	65	4	247	226	2200	3000
	280	65	4	247	226	2200	3000
120	150	16	1	24.5	28.0	3800	4500
	165	22	1.1	53.0	54.0	3600	4300
	165	22	1.1	53.0	54.0	3600	4300
	180	19	1	60.5	64.0	3400	4000
	180	19	1	60.5	64.0	3400	4000
	180	28	2	85.5	80.0	3400	4000
	180	28	2	85.5	80.0	3400	4000
	180	28	2	85.5	80.0	3400	4000
	215	40	2.1	154	130	2800	3400
	215	40	2.1	155	132	2800	3400
	215	40	2.1	154	130	2800	3400
	215	40	2.1	155	132	2800	3400
	260	55	3	217	196	2200	2800
	260	55	3	217	196	2200	2800
	260	55	3	217	196	2200	2800
	260	55	3	217	196	2200	2800
	260	55	3	217	196	2200	2800
	260	55	3	217	196	2200	2800
	260	55	3	217	196	2400	3000
	120.65	165.1	22.225	1.1	53.3	54.0	3600
121	165	22	1.1	53.3	54.0	3600	4300
127	228.6	34.925	2	148	133	2200	2800
130	165	18	1.1	37.0	38.0	3600	4300
	180	24	1.5	65.0	67.0	3400	4000

Designations	Abutment and fillet dimensions			Weight
	D _{smin}	dh _{max}	ra _{max}	
	mm			kg
6322/W124	124	226	2.5	9.72
IS-6322M	124	226	2.5	11.7
6322A	123	227	2.5	9.72
6322M	123	227	2.5	11.7
6322M/HQ1	124	226	2.5	10.5
6422	126	264	3	18.3
6422M	126	264	3	19.0
61824	125	145	1	0.566
61924	126.5	158.5	1	1.21
61924M	126.5	158.5	1	1.54
16024	125	175	1	1.64
16024M	125	175	1	1.82
6024	129	171	2	2.09
6024A	129	171	2	2.09
6024M	129	171	2	2.68
6224	131	204	2	5.28
6224/W124	132	203	2	5.30
6224M	131	204	2	6.68
6224M/CRA9	132	203	2	6.63
6324	133	247	2.5	12.5
6324-DT	133	247	2.5	12.5
6324A	133	247	2.5	12.5
6324M/C3	133	247	2.5	13.7
6324M-DT	133	247	2.5	14.8
6324F1/HQ1	133	247	2.5	13.4
6324/W124	134	245	2.5	12.5
619/121X4M	126.5	158.5	1	1.48
619/121M	126.5	158.5	1	1.48
66/127M	136	219.6	2	7.00
61826MA	136	159	1	0.969
61926M	138	172	1.5	1.92