Digital micrometers IP65

These digital micrometers have an IP65 classification and are therefore not only resistant to dust but can also withstand water jets. Also available as fast adjustable micrometers with a pitch of 2 mm.

- Measuring range: 0-300 mm.
- Resolution: 0.001 mm.
- mm/inch conversion.
- ABS/INC switchable.
- On/off switch.
- Automatic switch-off.

- Tungsten carbide measuring faces.
- Protection: IP65.
- DIN 863 T1.
- Power supply: 1 battery type V357.

Fast adjustable micrometers

 \blacksquare 1 revolution of the thimble = 2 mm.



| Item No. | Measuring range/mm | Accuracy mm | |
|----------|--------------------|----------------------------|--|
| 909.549 | 0 - 25 | ±0.002 | |
| 909.550 | 25 - 50 | ±0.002 | |
| 909.551 | 50 - 75 | ± 0.003 | |
| 909.552 | 75 - 100 | ± 0.003 | |
| 909.556 | 100 - 125 | ± 0.003 | |
| 909.557 | 125 - 150 | ± 0.003 | |
| 909.558 | 150 - 175 | ± 0.004 | |
| 909.559 | 175 - 200 | ± 0.004 | |
| 909.560 | 200 - 225 | ± 0.004 | |
| 909.561 | 225 - 250 | ± 0.004 | |
| 909.562 | 250 - 275 | ± 0.005 | |
| 909.563 | 275 - 300 | ± 0.005 ± 0.005 | |

| Option: | |
|---------|---------------|
| 836.535 | Spare battery |

Fast adjustable micrometers

| Item No. Measuring Accuracy | |
|--|--|
| range/mm mm | |
| 909.545 0 - 25 ±0.002 909.546 25 - 50 ±0.002 909.547 50 - 75 ±0.003 909.548 75 - 100 ±0.003 | |

Sets

| Item No. | Measuring range/mm | Pieces |
|----------|--------------------|--------|
| 909.577 | 0 - 75 | 3 |
| 909.578 | 0 - 100 | 4 |
| 909.579 | 0-150 | 6 |