

Internal measuring instruments

- Measuring range: 6-450 mm.
- Read-out depends on the type of dial indicator.
- Incl. standard dial indicator 0-3 mm/0.01 mm.
- Clamping shaft: $\varnothing 8$ mm.
- Self-centering (except 907.230).
- Interchangeable measuring inserts with tungsten carbide stylus tip (907.230 with spherical measuring face).
- Also suitable for various dial indicators from e.g. Mitutoyo, TESA, Käfer and Peacock with clamping stem $\varnothing 8$ mm.

Item No.	Measuring range/mm	Measuring depth/mm
907.230	6- 10	40
907.231	10- 18	100
907.232	18- 35	125
907.233	35- 50	150
907.235	50-160	150
907.236	160-250	400
907.237	250-450	400



907.235+907.933

NEW



910.004

Optional dial indicators

Item No.	Measuring range/mm	Read-out mm	Accuracy mm
Analog:			
907.933	0-10	0.01	-
Digital (with determination of the reversal point):			
907.879	0-12.7	0.001	± 0.01
907.878	0-12.7	0.001	± 0.005
909.250	0-12.5	0.002	± 0.015
909.251	0-12.5	0.001	± 0.006
910.004	0-12.7	0.001	± 0.004



907.879/878



909.250/251