

Screw thread micrometers

- Measuring range: 0 - 200 mm.
- Analog: graduation 0.01 mm, digital: resolution 0.001 mm.
- Insert shaft: $\varnothing 5$ mm.
- DIN 863 T3.
- Delivery incl. adjustment tools.
- From measuring range 25 - 50 mm including setting gauge 60° .

Analog

- Varnished frame.
- No-glare chrome finished thimble.

Digital

- mm/inch conversion.
- ABS/INC switchable.
- On/off switch.
- SET of minimum measurement value.
- No-glare chrome finished frame and thimble.
- Power supply: 1 battery type V357.



Analog, without measuring inserts

Item No.	Measuring range/mm	Accuracy mm
906.750	0 - 25	± 0.004
906.751	25 - 50	± 0.004
906.752	50 - 75	± 0.005
906.753	75 - 100	± 0.005
906.754	100 - 125	± 0.006
906.755	125 - 150	± 0.006
906.756	150 - 175	± 0.007
906.757	175 - 200	± 0.007

Digital, without measuring inserts

Item No.	Measuring range/mm	Accuracy mm
906.700	0 - 25	± 0.004
906.701	25 - 50	± 0.004
906.702	50 - 75	± 0.005
906.703	75 - 100	± 0.005
906.704	100 - 125	± 0.006
906.705	125 - 150	± 0.006
906.706	150 - 175	± 0.007
906.707	175 - 200	± 0.007

Option:

836.535 Spare battery