



Typ Typ	Abmessungen - Размеры									Tragzahlen (N) Коэффициент нагрузки (H)		Lager Подшипник	Gehäuse Корпус	Gewicht Вес	
	d	h	w	b	c	a	l	B	S	dynamisch C Динамическая C	statisch C ₀ Статическая C ₀				kg
	mm/Zoll - мм/дюйм														
UKECH205+H2305	20	64	103	78	0	40	19	34,1				UK205+H2305	ECH205	0,9	
UKECH205+HE2305	¾	233/64	41/16	35/64	0	137/64	¾	1,3425	G¾	13300	7457				UK205+HE2305
UKECH206+H2306	25	64	103	78	0	40	19	38,1				UK206+H2306	ECH206	0,9	
UKECH206+HS2306	7/8	233/64	41/16	35/64	0	137/64	¾	1,5000	G¾	18525	10735				UK206+HS2306
UKECH206+HE2306	1											UK206+HE2306			
UKECH207+H2307	30	70	116	92	0	40	19	42,9				UK207+H2307	ECH207	1,23	
UKECH207+HS2307	11/8	2¾	49/16	35/8	0	137/64	¾	1,6890	G¾	24415	14630				UK207+HS2307
UKECH208+H2308	35	73	121	96	2	40	19	49,2				UK208+H2308	ECH208	1,32	
UKECH208+HE2308	1¼	27/8	449/64	325/32	5/64	137/64	¾	1,9370	G¾	27645	16910				UK208+HE2308
UKECH208+HS2308	13/8											UK208+HS2308			
UKECH209+H2309	40	82	136	108	5	48	21	49,2				UK209+H2309	ECH209	1,79	
UKECH209+HA2309	17/16														UK209+HA2309
UKECH209+HE2309	1½	315/64	523/64	4¼	13/64	157/64	53/64	1,9370	G1	32395	20235	UK209+HE2309			
UKECH209+HS2309	15/8											UK209+HS2309			
UKECH210+H2310	45	83	142	118	5	48	21	51,6				UK210+H2310	ECH210	2,19	
UKECH210+HS2310	15/8														UK210+HS2310
UKECH210+HA2310	111/16	317/64	519/32	441/64	13/64	157/64	53/64	2,0315	G1	33345	22135	UK210+HA2310			
UKECH210+HE2310	1¾											UK210+HE2310			
UKECH211+H2311	50	87	150	126	7	60	25	55,6				UK211+H2311	ECH211	2,84	
UKECH211+HS2311	17/8														UK211+HS2311
UKECH211+HA2311	115/16	327/64	529/32	461/64	9/32	223/64	63/64	2,1890	G1¼	41230	27930	UK211+HA2311			
UKECH211+HE2311	2											UK211+HE2311			
UKECH212+H2312	55	102	173	142	9	60	28	65,1				UK212+H2312	ECH212	3,81	
UKECH212+HS2312	21/8	41/64	613/16	519/32	23/64	223/64	17/64	2,5630	G1¼	49780	34390				UK212+HS2312

Spannhülsen HA; HE; HS mit Zollgewinde

Втулки HA; HE; HS с дюймовой резьбой

S - Auf Anfrage mit metrischem, Zoll- und Gasgewinde lieferbar

S - На заказ поставляется с метрической, дюймовой и газовой резьбой