

A230 - Red Steam Hose to BS5342:1986: A2 18 bar



| | |
|---------------------------|---|
| Application: | Steam hose for handling SUPERHEATED STEAM and manufactured in accordance with BS5342:1986:A2. Widely used in petrochemical plants/referies for maintenance and pipe insulation during freezing weather conditions. Avoid excessive contamination with oil |
| Working pressure: | 18 bar (261 psi). Safety factor 10:1 |
| Lining: | Extruded black EPDM |
| Reinforcement: | High tensile brass coated stranded steel wire |
| Cover: | Red EPDM, pin pricked |
| Branding: | Emboss brand DIXON A230 STEAM 18 BAR SF 10:1 210°C BS5342 A2 1986 DRAIN AFTER USE DATE OF MANUFACTURE DIXON ASSEMBLY W.P. _____ |
| Temperature range: | -20°C to + 210°C and intermittent to 232°C |

F

| PART NUMBER | DIMENSIONS MM | | PRESSURE BAR | | WEIGHT KG/M (APPROXIMATE) | BEND RADIUS MM (APPROXIMATE) | COIL LENGTH METRE |
|-------------|---------------|----|--------------|-------------|---------------------------|------------------------------|-------------------|
| | ID | OD | WORKING | BURST (MIN) | | | |
| A230012 | 13 | 27 | 18 | 180 | 0.50 | 52 | 40 |
| A230020 | 19 | 33 | 18 | 180 | 0.70 | 76 | 40 |
| A230025 | 25 | 40 | 18 | 180 | 0.90 | 100 | 40 |
| A230032 | 32 | 46 | 18 | 180 | 1.30 | 128 | 40 |
| A230038 | 38 | 54 | 18 | 180 | 1.65 | 152 | 40 |
| A230050 | 51 | 68 | 18 | 180 | 2.20 | 200 | 40 |

STEAM IS DANGEROUS.

WE STRONGLY RECOMMEND THE USE OF GENUINE DIXON BOSS STEAM COUPLINGS & CLAMPS.

DO NOT COMPROMISE SAFETY.

FOR INSTALLATION & SAFETY GUIDELINES REFER TO THE TECHNICAL SECTION