

# Quick Release Couplings

## T-Series High Pressure Screw-Together

- Threaded sleeve allows connection and disconnection while coupler and/or nipple are under pressure
- Urethane seal resists extrusion under high pressure during connection and disconnection



PERFORMANCE SPECIFICATIONS	OPERATING bar (psi)	MIN. BURST bar (psi)	FLOW RATE $\Delta P=3$ bar	LOCKING MECHANISM
1/4"	690 (10,000)	2,069 (30,000)	11 LPM (3 GPM)	Threaded
3/8"	690 (10,000)	2,069 (30,000)	23 LPM (6 GPM)	Threaded

Please Note: Divide Minimum Burst Pressure by four (4) for dynamic applications.

'T' SERIES INTERCHANGE	PARKER	STUCCHI	ENERPAC	HOLMBURY	FASTER
1/4"	Series 3000	IVHP	-	HPA Series	PVVM Series
3/8"	Series 3000	IVHP	C-604	HPA Series	PVVM Series



(Male Thread)

T-SERIES ENERPAC INTERCHANGE (COUPLER)			
PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
2TM2	1/4"	1/4"-18 NPTF	Steel
2TBM2	1/4"	R1/4" BSPT	Steel
3TM3	3/8"	3/8"-18 NPTF	Steel
3TM3-SS	3/8"	3/8"-18 NPTF	316 SS
3TBM3	3/8"	R3/8" BSPT	Steel



(Female Thread)

T-SERIES ENERPAC INTERCHANGE (COUPLER)			
PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
3TF3	3/8"	3/8"-18 NPTF	Steel



(Female Thread)

T-SERIES ENERPAC INTERCHANGE (NIPPLE)			
PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
T2F2	1/4"	1/4"-18 NPTF	Steel
T2BF2	1/4"	G1/4" BSPP	Steel
T3F3	3/8"	3/8"-18 NPTF	Steel
T3F3-SS	3/8"	3/8"-18 NPTF	316 SS
T3BF3	3/8"	G3/8" BSPP	Steel



T-SERIES ENERPAC INTERCHANGE (COUPLER DUST PLUG)			
PART NO.	BODY SIZE	CAP LANYARD	BODY MATERIAL
2TDP	1/4"	Elastomer	Steel
3TDP	3/8"	Elastomer	Steel



T-SERIES ENERPAC INTERCHANGE (NIPPLE DUST CAP)			
PART NO.	BODY SIZE	CAP LANYARD	BODY MATERIAL
T2DC	1/4"	Chain	Steel
T3DC	3/8"	Chain	Steel