

# Inside micrometers with interchangeable anvils

Screw thread micrometers for internal measurements of pitch diameters. The interchangeable anvils allow measurements of several kinds of screw thread.

- Measuring range: 75 - 300 mm.
- Graduation: 0.01 mm.
- Insert shaft:  $\varnothing 5$  mm.
- Delivery incl. setting gauge for metric thread, 60° flank angle.



Item No.	Measuring range/mm	Accuracy mm
<b>Inside micrometers without inserts:</b>		
906.924	75 - 100	$\pm 0.025$
906.925	100 - 125	$\pm 0.028$
906.926	125 - 150	$\pm 0.030$
906.927	150 - 175	$\pm 0.033$
906.928	175 - 200	$\pm 0.035$
906.929	200 - 225	$\pm 0.038$
906.930	225 - 250	$\pm 0.040$
906.931	250 - 275	$\pm 0.043$
906.932	275 - 300	$\pm 0.045$

Item No.	Threads per inch	--
<b>Inserts for Whitworth threads, 55° flank angle, per pair:</b>		
906.940	60	-48
906.941	48	-40
906.942	40	-32
906.944	32	-24
906.945	24	-18
906.946	18	-14
906.947	14	-10
906.948	10	-7
906.949	7	-4.5
906.950	4.5	-3.5
906.951	Set 60 - 3.5	

Item No.	Pitch/mm	----
<b>Inserts for metric threads, 60° flank angle, per pair:</b>		
906.933	0.4 - 0.5	
906.934	0.6 - 0.9	
906.935	1 - 1.75	
906.936	2 - 3	
906.937	3.5 - 5	
906.938	5.5 - 7	
906.939	Set 0.4 - 7	

Item No.	Threads per inch	----
<b>Inserts for UN, UNC and UNF threads, 60° flank angle, per pair:</b>		
906.952	64	-48
906.953	44	-28
906.954	24	-14
906.955	13	-9
906.956	8	-5
906.957	4.5	-3.5
906.958	Set 64 - 3.5	