

## Digital dial indicators

Digital dial indicators with digital and digital-analog read-out.

- Measuring range: 0 - 12.5 mm.
  - Resolution: 0.002 or 0.001 mm.
  - mm/inch conversion.
  - ABS/INC switchable.
  - On/off switch.
  - Automatic switch-off.
  - Reset/preset.
  - Clamping stem:  $\varnothing$  8 mm.
  - Dial diameter: 62 mm.
  - Dial 360° rotatable.
  - Reversible measuring direction.
- With determination of the reversal point.
  - Adjustable tolerance limits.
  - Power supply: 1 battery type CR2032.



Item No.	Measuring range/mm	Resolution mm	Accuracy mm	Measuring force/N
909.250	0 - 12.5	0.002	$\pm 0.015$	1.8 - 3.0
909.251	0 - 12.5	0.001	$\pm 0.006$	2.2 - 3.5
<b>Option:</b> 495.157 Spare battery				

## Digital dial indicators

Universal digital indicators with both digital and digital-analog display of the measuring value, and can also be rotated over 340° to ensure easy read-out in all positions.

- Measuring range: 0 - 12.7 mm.
  - Resolution: 0.001 mm.
  - Analog resolution: 0.001/0.002/0.01/0.02/0.05 mm.
  - mm/inch conversion.
  - ABS/INC switchable.
  - On/off switch.
  - Automatic switch-off.
  - Reset/preset.
  - Clamping stem:  $\varnothing$  8 mm.
  - Dial diameter: 61 mm.
  - Dial 340° rotatable.
  - Reversible measuring direction.
- With determination of the reversal point.
  - Adjustable tolerance limits.
  - Protection: IP54.
  - Power supply: 1 battery type CR2032.



Item No.	Measuring range/mm	Accuracy mm
907.879	0 - 12.7	$\pm 0.01$
907.878	0 - 12.7	$\pm 0.005$
<b>Option:</b> 495.157 Spare battery		