

Screw thread micrometers

- Measuring range: 0 - 200 mm.
- Analog: graduation 0.01 mm, digital: resolution 0.001 mm.
- Insert shaft: $\varnothing 5$ mm.
- DIN 863 T3.
- Delivery incl. adjustment tools.
- From measuring range 25 - 50 mm including setting gauge 60° .
- No-glare chrome finished thimble.

Digital

- mm/inch conversion.
- ABS/INC switchable.
- On/off switch.
- Reset/preset.
- Protection: IP65.
- Power supply: 1 battery type V357.



906.751



909.889

Analog, without measuring inserts

Item No.	Measuring range/mm	Accuracy mm	Price EUR
906.750	0 - 25	± 0.004	70.00
906.751	25 - 50	± 0.004	77.00
906.752	50 - 75	± 0.005	90.00
906.753	75 - 100	± 0.005	98.00
906.754	100 - 125	± 0.006	112.00
906.755	125 - 150	± 0.006	126.00
906.756	150 - 175	± 0.007	139.00
906.757	175 - 200	± 0.007	153.00

Digital, without measuring inserts

Item No.	Measuring range/mm	Accuracy mm	Price EUR
909.889	0 - 25	± 0.004	126.00
909.890	25 - 50	± 0.004	136.00
909.891	50 - 75	± 0.005	147.00
909.892	75 - 100	± 0.005	160.00
909.893	100 - 125	± 0.006	235.00
909.894	125 - 150	± 0.006	255.00
909.895	150 - 175	± 0.007	278.00
909.896	175 - 200	± 0.007	304.00

Option:

836.535 Spare battery 1.90

