

### TESA ISOMASTER Standard Models with Analogue Indication

Slanted full millimetres on the barrel are set apart from the straight half millimetres to virtually eliminate reading errors.

The knurled sleeve needs only to be reversed to render the friction drive built into the thimble inactive.



| No       | mm        | mm   |
|----------|-----------|------|
| 00110101 | 0 ÷ 25    | 0,01 |
| 00110102 | 25 ÷ 50   | 0,01 |
| 00110103 | 50 ÷ 75   | 0,01 |
| 00110104 | 75 ÷ 100  | 0,01 |
| 00110105 | 100 ÷ 125 | 0,01 |
| 00110106 | 125 ÷ 150 | 0,01 |
| 00110107 | 150 ÷ 175 | 0,01 |
| 00110108 | 175 ÷ 200 | 0,01 |
| 00110109 | 200 ÷ 225 | 0,01 |
| 00110110 | 225 ÷ 250 | 0,01 |
| 00110111 | 250 ÷ 275 | 0,01 |
| 00110112 | 275 ÷ 300 | 0,01 |

- DIN 863 T1 NFE 11-095
- Tungsten carbide tipped
- Plastic case
- Measuring range 0 to 100 mm with inspection report and declaration of conformity
- Measuring range smaller than 100 mm with a declaration of conformity
- Identification number
- 0.5 mm
- Max. 10 N
- ≤ 100 mm: Ø 6,5 mm  
> 100 ≤ 300 mm: Ø 8 mm

### Set of 4 TESA ISOMASTER Micrometers

The models covering application range 0 to 100 mm provide the quality that you need at competitive prices.



| No                    | =  | mm      |
|-----------------------|--|---------|
| 00110113              | Set of 4 ISOMASTER micrometers   | 0 ÷ 100 |
| <b>CONSISTING OF:</b> |  |         |
| 00110101              | ISOMASTER AA external micrometer with vernier scale, 0 ÷ 25 mm and resolution to 0,01 mm   |         |
| 00110102              | ISOMASTER AA external micrometer with vernier scale, 25 ÷ 50 mm and resolution to 0,01 mm  |         |
| 00110103              | ISOMASTER AA external micrometer with vernier scale, 50 ÷ 75 mm and resolution to 0,01 mm  |         |
| 00110104              | ISOMASTER AA external micrometer with vernier scale, 75 ÷ 100 mm and resolution to 0,01 mm |         |

- 
- Plastic case