

Fisso Classic Line dial indicator stands

These dial indicator stands are manufactured according to the classic principle with chrome plated arm parts, joint together with the three hinge points by means of a central mechanic clamping device. Because this is done with one on/off switch control, the stand can be positioned easily and precisely.

- Fine adjustment: with clamping shaft $\varnothing 8$ mm (for dial indicators and probes) and dovetail joint (for lever-type dial test indicators).
- Dial indicator not included.
- Various bases, fine adjustments and other accessories available; see “Fisso dial indicator stand accessories”.

Complete stands (incl. base and fine adjustment)

Item No.	Arm length/mm	Base type*	Magnetic force/N
837.262	200	M	800
837.263	200	AM	600
837.290	200	AMO	600
837.264	200	TM	300
837.237	200	V	–
837.245	280	M	800
837.265	280	SM	1000
837.238	280	V	–
837.287	450	SM	1000
837.266	450	MM	1500
837.246	630	MM	1500

* For an extensive description of the base types see “Fisso dial indicator stand accessories”.



Item No.	Arm length/mm	Thread of head	Thread of base	Item No.
Separate arm without fine adjustment:				With fine adjustment:
837.283	197	M6	M8	837.267
837.284	288	M6	M8	837.252
837.285	453	M8	M8	837.268
837.286	635	M8	M10 x 1.25	837.253